

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A display device being a hold type display device which holds a brightness of the antecedent picture until the subsequent signal is inputted to a pixel, wherein:

a frame displaying one picture is time-divided into multiple sub-frames; and

a brightness of ~~[[a]]~~ each subsequent sub-frame of said frame is attenuated at a same designated ratio with respect to a brightness of a preceding sub-frame ~~according to a brightness of an inputted picture.~~

2. (original) A display device comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient; and

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame.

3. (original) A display device being a hold type display device which holds a brightness of the antecedent picture until the subsequent signal is inputted to a pixel, wherein:

a frame displaying one picture is time-divided into multiple sub-frames; and

the brightness of the subsequent sub-frame is attenuated at a designated ratio according to the brightness of inputted picture, comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient; and

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame.

4. (original) A display device comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient; and

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the

relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame, wherein:

the attenuation signal generating means generates a signal by shifting the series of a digitalized luminosity signal in the direction of the low order digit and eliminating the digits which are underflowed due to the shift, and outputs the generated signal as the attenuation signal.

5. (original) A display device being a hold type display device which holds the brightness of the antecedent picture until the subsequent signal is inputted to a pixel, comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient; and

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame, wherein:

a frame displaying one picture is time-divided into multiple sub-frames;

the brightness of the subsequent sub-frame is attenuated at a designated ratio according to the brightness of inputted picture; and

the attenuation signal generating means generates a signal by shifting the series of a digitalized luminosity signal in the direction of the low order digit and eliminating the digits which are underflowed due to the shift, and outputs the generated signal as the attenuation signal.

6. (original) A display device comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient;

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame;

an integration means for integrating the luminosity signals of entire pixels which form a picture in the relevant frame; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the obtained integrated value.

7. (original) A display device being a hold type display device which holds the brightness of the antecedent picture until the subsequent signal is inputted to a pixel, wherein:

a frame displaying one picture is time-divided into multiple sub-frames, and

the brightness of the subsequent sub-frame is attenuated at a designated ratio according to the brightness of inputted picture, comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient;

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame;

an integration means for integrating the luminosity signals of entire pixels which form a picture in the relevant frame; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the obtained integrated value.

8. (original) A display device comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient;

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame;

an integration means for integrating the luminosity signals of entire pixels which form a picture in the relevant frame; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the obtained integrated value, wherein:

the attenuation signal generating means generates a signal by shifting the series of a digitalized luminosity signal in the direction of the low order digit and eliminating the digits which are underflowed due to the shift, and outputs the generated signal as the attenuation signal.

9. (original) A display device being a hold type display device which holds the brightness of the antecedent picture until the subsequent signal is inputted to a pixel, comprising:

a sub-frame generating means which time-divides a frame displaying one picture into multiple sub-frames;

an attenuation signal generating means for generating an attenuation signal by dividing an inputted luminosity signal by a designated attenuation coefficient;

a signal switching means for inputting the luminosity signal before division to the antecedent sub-frame in the relevant frame, and inputting the attenuation signal after division to the subsequent sub-frame in the relevant frame;

an integration means for integrating the luminosity signals of entire pixels which form a picture in the relevant frame; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the obtained integrated value, wherein:

a frame displaying one picture is time-divided into multiple sub-frames;

the brightness of the subsequent sub-frame is attenuated at a designated ratio according to the brightness of inputted picture; and

the attenuation signal generating means generates a signal by shifting the series of a digitalized luminosity signal in the direction of the low order digit and eliminating the digits which are underflowed due to the shift, and outputs the generated signal as the attenuation signal.

10. (original) A display device as claimed in claim 2 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.

11. (original) A display device as claimed in claim 3 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.

12. (original) A display device as claimed in claim 4 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.



13. (original) A display device as claimed in claim 5 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.

14. (original) A display device as claimed in claim 6 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.

15. (original) A display device as claimed in claim 7 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.

16. (original) A display device as claimed in claim 8 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.

17. (original) A display device as claimed in claim 9 comprising:

a luminosity classifying means for segmenting the inputted luminosity signals according to the luminosity level; and

an attenuation coefficient generating means for generating an attenuation coefficient which is varied according to the segmented brightness range.